Philips
LCD widescreen monitor

19.1" wide
WXGA+

190CW7CS

Best value for money widescreen LCD monitor

Enjoy more with this big widescreen! Experience multiple viewing experiences on a single screen with the Philips 190CW7's fast response time and convenient one touch auto adjustment - all in one easy-to-use, highly affordable package.

Outstanding front of screen performance

- Empowered for Windows Vista
- Big, wide screen: IM, write mail, watch videos on one screen
- 5ms fast response time
- WXGA+, wide format 1440 x 900 resolution for sharper display
- sRGB ensures color matching between display and printouts

Green design

- For your safety: Aerospace composite fire retardant case
- Lead-free design safeguards our environment
- Power consumption below the industry average

Great convenience

- One-touch brightness and contrast controls
- Embedded power supply eliminates external power adaptors
- Auto adjustment for perfect picture display with one touch
- Easy, user friendly plug-and-play installation

PHILIPS
sense and simplicity

LCD widescreen monitor
19.1" wide WXGA+

190CW7CS/96

Specifications

Picture/Display
- LCD panel type: 1440 x 900 pixels, Anti-glare polarizer, RGB vertical stripe
- Panel Size: 19.1"/ 48.1 cm
- Effective viewing area: 410.4 x 256.5 mm
- Pixel pitch: 0.285 x 0.285 mm
- Brightness: 300 cd/m²
- Contrast ratio (typical): 850:1
- Display colors: 16.7 M
- Viewing angle: 170° (H) / 160° (V), @ C/R > 10
- Response time (typical): 5 ms
- Maximum Resolution: 1440 x 900 @ 75 Hz
- Optimum Resolution: 1440 x 900 @ 60 Hz
- Video Dot Rate: 140 MHz
- Horizontal Scanning Frequency: 30 - 83 kHz
- Vertical Scanning Frequency: 55 - 75 Hz
- sRGB

Connectivity
- Signal Input: VGA (Analog)
- Video Sync Input Signal: Composite Sync, Separate Sync, Sync on Green

Convenience
- User convenience: On-screen Display
- Monitor Controls: Auto, Brightness (Left), Contrast (Right), Menu (OK), Power On/Off
- OSD Languages: English, French, German, Italian, Simplified Chinese, Spanish
- Other convenience: Kensington lock compatible
- Plug & Play Compatibility: DDC 2B, Windows 98/ ME/2000/XP/Vista
- Regulatory Approvals: CE Mark, E2000, EMC, Energy Star, FCC-B, UL, CSA, MPRII, TCO '99, TÜV/GS, TÜV Ergo
- Tilt: -5° to 20°

Accessories
- Included Accessories: AC Power Cord, VGA cable
- User Manual

Dimensions
- Box dimensions (W x H x D): 520 x 392 x 190 mm
- Box dimensions in inch (W x H x D): 20.5 x 15.4 x 7.5 inch
- Set dimensions (W x H x D): 438.5 x 310.4 x 60.5 mm
- Set dimensions in inch (W x H x D): 17.3 x 12.2 x 2.4 inch
- Set dimensions with stand (W x H x D): 438.5 x 358 x 211 mm
- Set dimensions with stand in inch (W x H x D): 17.3 x 14.1 x 8.3 inch
- MTBF: 50,000 (excl. CCFL 40,000) hrs
- Relative humidity: 20% - 80%
- Temperature range (operation): 0°C to 40°C
- Temperature range (storage): -20°C to 60°C
- Product weight (+stand): 5 kg
- Product weight (+stand) (lb): 11 lb
- Weight incl. Packaging: 6.7 kg
- Weight incl. Packaging (lb): 14.8 lb

Power
- Complies with: E2000, Energy Star
- Consumption (On mode): 36W (Typical)
- Consumption (Off Mode): < 1 W
- Power LED indicator: Operation - green, Stand by/sleep - Amber
- Power supply: Built-in, 100-240VAC, 50/60Hz

Product highlights

Windows Vista ready
Philips Vista-ready monitors are empowered for vibrant, exciting display of this new, visually sophisticated and demanding Windows operating system, designed to enhance your entertainment experience, make you more productive and help you control your computing experience at home and in the office, making viewing, finding and organizing information for work or play quick, efficient and easy.

Widescreen design
A wide screen has a wider aspect ratio for displaying more entertainment or information to have more fun and get more done.

5ms on/off response time
On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

WXGA+ 1440 x 900 resolution
WXGA+ or Wide Extended Graphics Array plus is a standard indicating a graphics monitor's ability to display up to the resolutions 1440 by 900 pixels and supports simultaneous display of more than one million colors. WXGA allows monitors to be non-interlaced for better display performance and increased color accuracy.

sRGB ready
sRGB is an industry standard that ensures the best possible match between the colors displayed on your screen and those in your printouts.

Flame retardant cabinet
PC/ABS plastic composite is the industry's best and toughest flame-retardant casing material; and is a space-age compound deployed in the aerospace and automotive industries as well as in fire detectors that is compliant with most stringent fire safety standards.

Lead-free
Lead-free display products are designed and produced in compliance with strict European Community Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm the environment.

Lower power consumption
Reduction of the electrical power required to operate a device.

Brightness and contrast button
Conveniently located buttons on the front bezel that provide one-touch brightness and contrast adjustments.

Embedded power supply
An embedded power supply is a power adaptor built into the body of a display device that replaces a bulky external power adaptor.

One-touch auto adjustment
The auto adjustment key restores optimal screen position, phase and clock settings with the press of a single button - without navigation through OSD menus and control keys.

Easy plug-and-play
Plug-and-play is a peripheral connectivity standard. A plug and play display device can be connected to a PC and operate without requiring user intervention to adjust complicated settings.

Issue date 2009-01-29

Version: 5.0.13

12 NC: 8639 000 17261
EAN: 87 10895 98982 4

© 2009 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com